

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Name : Ampreg 30 Resin  
UFI : X3E8-W2Q9-V00Q-QS31  
Product code : 19196  
Type of product : Epoxy resin  
Product group : Resin

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Gurit (UK) Ltd  
St Cross Business Park Newport  
GBR- PO30 5WU Isle of Wight  
United Kingdom  
T +44 (0) 1983 828 000 (All Technical and Commercial Enquiries)  
[Regulatory@Gurit.com](mailto:Regulatory@Gurit.com) - [www.gurit.com](http://www.gurit.com)

##### Other

Gurit (Spain) Ltd  
Polígono Industrial Romica C/K Parcela 11C, APDO.447  
ESP- 02080 Albacete  
Spain  
T +34 967 254 507 - F +34 967 254 005  
[Regulatory@gurit.com](mailto:Regulatory@gurit.com) - [www.Gurit.com](http://www.Gurit.com)

#### 1.4. Emergency telephone number

Emergency number : Carechem 24Hrs: +44 (0) 1273 289451  
Telephone number for use in case of chemical exposure, spillage or fire only.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS09

Signal word (CLP) :

Warning

Contains :

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700), Formaldehyde, polymer with (chloromethyl)oxirane and phenol, oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

# Ampreg 30 Resin

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves. P302+P352 - IF ON SKIN: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 - Specific treatment (see supplemental first aid instruction on this label).

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ )	CAS-No.: 1675-54-3 EC-No.: 216-823-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119456619-26	$\geq 50$	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Formaldehyde, polymer with (chloromethyl)oxirane and phenol	CAS-No.: 9003-36-5 EC-No.: 500-006-8 REACH-no: 01-2119454392-40	10 – 25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute Not classified Aquatic Chronic 2, H411
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS-No.: 68609-97-2 EC-No.: 271-846-8 EC Index-No.: 603-103-00-4 REACH-no: 01-2119485289-22	5 – 10	Skin Irrit. 2, H315 Skin Sens. 1, H317

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ )	CAS-No.: 1675-54-3 EC-No.: 216-823-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119456619-26	( $5 \leq C < 100$ ) Skin Irrit. 2, H315 ( $5 \leq C < 100$ ) Eye Irrit. 2, H319

Full text of H- and EUH-statements: see section 16

# Ampreg 30 Resin

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Collect contaminated fire fighting water separately. It must not enter drains.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing vapours.
----------------------	---

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

# Ampreg 30 Resin

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing vapours.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool.
Maximum storage period	: 2 year
Storage temperature	: ≤ 30 °C Storage at elevated temperatures may cause pressure build-up in sealed containers
Storage area	: Store away from heat. Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

No additional information available

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

No additional information available

##### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

##### 8.2.1. Appropriate engineering controls

###### Appropriate engineering controls:

Ensure good ventilation of the work station.

##### 8.2.2. Personal protection equipment

###### Personal protective equipment symbol(s):



###### 8.2.2.1. Eye and face protection

###### Eye protection:

Safety glasses

###### 8.2.2.2. Skin protection

###### Skin and body protection:

Wear suitable protective clothing

# Ampreg 30 Resin

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin and body protection	
Type	Standard
Tyvek® Gown/Coveralls	EN 13034

### Hand protection:

Protective gloves. Time of penetration is to be checked with the glove producer

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	0 (< 10 minutes)	0.26mm		EN ISO 374

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Respiratory protection			
Device	Filter type	Condition	Standard
Disposable half mask	Gas/vapour filter	Vapour protection	EN 405

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Industrial and professional. Perform risk assessment prior to use. Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Appearance	: Yellow liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 158 °C BS EN ISO 2719: 2002
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: ≈ 5
Viscosity, kinematic	: 21,739 mm <sup>2</sup> /s
Viscosity, dynamic	: 25 °C
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available

# Ampreg 30 Resin

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Density	: 1,15 g/cm <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 0,8 – 1,3 g/l Directive 2004/42/CE

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rat	> 2000 mg/kg
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
LD50 oral rat	17100 mg/kg
LD50 oral	26,8 g/kg
LD50 dermal rabbit	> 4000 mg/kg

# Ampreg 30 Resin

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin corrosion/irritation : Causes skin irritation.  
pH: ≈ 5

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

pH 6,12 – 6,64

Serious eye damage/irritation : Causes serious eye irritation.  
pH: ≈ 5

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

pH 6,12 – 6,64

Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

IARC group 3 - Not classifiable

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

NOAEL (chronic, oral, animal/male, 2 years) 15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other., Remarks on results: other:

NOAEL (chronic, oral, animal/female, 2 years) 100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other., Remarks on results: other:

Reproductive toxicity : Not classified

### oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

NOAEL (animal/female, F1) 200 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.4420 (Preliminary Developmental Toxicity Screen)

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

### Ampreg 30 Resin

Viscosity, kinematic 21,739 mm<sup>2</sup>/s

## 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

LC50 - Fish [1] 1,2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)

LC50 - Fish [2] 2 mg/l

EC50 72h - Algae [1] 9,4 mg/l Test organisms (species): Scenedesmus capricornutum

# Ampreg 30 Resin

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (1675-54-3)

EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)

LC50 - Fish [1]	< 1 mg/l
-----------------	----------

## 12.2. Persistence and degradability

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (1675-54-3)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

## 12.3. Bioaccumulative potential

### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (1675-54-3)

Bioaccumulative potential	Not established.
---------------------------	------------------

## 12.4. Mobility in soil

No additional information available

## 12.5. Results of PBT and vPvB assessment

No additional information available

## 12.6. Endocrine disrupting properties

No additional information available

## 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA




ADR	IMDG	IATA
<b>14.1. UN number or ID number</b>		
UN 3082	UN 3082	UN 3082



# Ampreg 30 Resin

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA
<b>14.2. UN proper shipping name</b>		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.
<b>Transport document description</b>		
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 9, III
<b>14.3. Transport hazard class(es)</b>		
9	9	9
		
<b>14.4. Packing group</b>		
III	III	III
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available		

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90

# Ampreg 30 Resin

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Orange plates : 

Tunnel restriction code (ADR) : -  
EAC code : •3Z

### Transport by sea

Special provisions (IMDG) : 274, 335, 969  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : LP01, P001  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP2, TP29  
EmS-No. (Fire) : F-A  
EmS-No. (Spillage) : S-F  
Stowage category (IMDG) : A

### Air transport

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y964  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 964  
PCA max net quantity (IATA) : 450L  
CAO packing instructions (IATA) : 964  
CAO max net quantity (IATA) : 450L  
Special provisions (IATA) : A97, A158, A197  
ERG code (IATA) : 9L

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### VOC Directive (2004/42)

VOC content : 0,8 – 1,3 g/l Directive 2004/42/CE

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

# Ampreg 30 Resin

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
	Display additional SDS EU addresses	Added	
1.1	Product code	Added	
1.1	Trade name	Modified	
1.2	Main use category	Modified	
2.2	Precautionary statements (CLP)	Modified	
8.2	Hand protection	Modified	

Full text of H- and EUH-statements:	
Aquatic Acute Not classified	Hazardous to the aquatic environment – Acute Hazard Not classified
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. The information contained within this document is Gurit copyright and any distribution or publication beyond the recipient's organisation is prohibited without Gurit's prior written consent.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Name : Ampreg 3X Slow Hardener  
Type of product : Hardener (Crosslinker)  
Product group : Hardener

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use  
Industrial/Professional use spec : Industrial  
For professional use only

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Gurit (UK) Ltd  
St Cross Business Park  
Newport  
PO30 5WU Isle of Wight - United Kingdom  
T +44 (0) 1983 828 000 (All Technical and Commercial Enquiries)  
[Regulatory@gurit.com](mailto:Regulatory@gurit.com) - [www.gurit.com](http://www.gurit.com)

#### 1.4. Emergency telephone number

Emergency number : Carechem 24: +44 (0) 1273 289451 24 Hours  
Telephone number for use in case of chemical exposure, spillage or fire only.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

Signal word (CLP) :

Danger

Hazardous ingredients :

benzyl alcohol; Amines, polyethylenepoly-, triethylenetetramine fraction; 2,4,6-tris(dimethylaminomethyl)phenol; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 1,5-Pentanediamine, 2-methyl-; Propylene glycol diamine, 2-amino-, diether with Propylene

# Ampreg 3X Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)	: H302 - Harmful if swallowed. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P270 - Do not eat, drink or smoke when using this product. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Propylene glycol diamine, 2-amino-, diether with Propylene	(CAS-No.) 9046-10-0 (REACH-no) 01-2119557899-12	25 – 50	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
3-aminomethyl-3,5,5-trimethylcyclohexylamine	(CAS-No.) 2855-13-2 (EC-No.) 220-666-8 (EC Index-No.) 612-067-00-9 (REACH-no) 01-2119514687-32	25 – 50	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
1,5-Pentanediamine, 2-methyl-	(CAS-No.) 15520-10-2 (EC-No.) 239-556-6 (REACH-no) 01-2119976310-41	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 STOT SE 3, H335
Amines, polyethylenepoly-, triethylenetetramine fraction	(CAS-No.) 112-24-3; 90640-67-8 (EC-No.) 292-588-2 (REACH-no) 01-2119487919-13	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9 (EC Index-No.) 603-069-00-0 (REACH-no) 01-2119560597-27	1 – 3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
benzyl alcohol	(CAS-No.) 100-51-6 (EC-No.) 202-859-9 (EC Index-No.) 603-057-00-5 (REACH-no) 01-2119492630-38	< 3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 3 (Inhalation:vapour), H331 Eye Irrit. 2, H319

Full text of H-statements: see section 16

# Ampreg 3X Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

#### 5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area.
Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Collect contaminated fire fighting water separately. It must not enter drains.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: Protective clothing.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe vapours.

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

# Ampreg 3X Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe vapours. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.
Storage temperature	: ≤ 30 °C Possible pressure build-up
Storage area	: Store away from heat. Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

<b>Hand protection:</b>					
Protective gloves					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)				EN ISO 374

<b>Eye protection:</b>					
Safety glasses					

<b>Skin and body protection:</b>					
Wear suitable protective clothing					
Type	Standard				
Tyvek® Gown/Coveralls	EN 13034				

<b>Respiratory protection:</b>					
In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended					

# Ampreg 3X Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Device	Filter type	Condition	Standard
Disposable half mask	Gas/vapour filter	Vapour protection	EN 405

### Personal protective equipment symbol(s):



### Environmental exposure controls:

Avoid release to the environment.

### Other information:

Industrial and professional. Perform risk assessment prior to use. Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Yellow.
Odour	: Amine-like.
Odour threshold	: No data available
pH	: ≈ 11
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: ≈ 156 °C (estimated value)
Flash point	: 108.5 °C Closed cup
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.94 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 25 °C
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.



# Ampreg 3X Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Ampreg 3X Slow Hardener

ATE CLP (oral)	1444.93 mg/kg bodyweight
----------------	--------------------------

#### Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)

LD50 oral rat	1716.2 mg/kg bodyweight
LD50 dermal rabbit	1465.4 mg/kg bodyweight

#### 2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

LD50 oral rat	1200 mg/kg
LD50 dermal rat	1280 mg/kg

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

LD50 oral rat	1030 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	5.01 mg/l/4h

#### 1,5-Pentanediamine, 2-methyl- (15520-10-2)

LD50 oral rat	1170 mg/kg
LD50 dermal rabbit	1870 mg/kg

#### Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)

LD50 oral rat	2885 mg/kg
LD50 dermal rabbit	2980 mg/kg

#### benzyl alcohol (100-51-6)

LD50 oral rat	1620 mg/kg
LD50 dermal rabbit	2 g/kg
LC50 inhalation rat (mg/l)	5400 mg/m <sup>3</sup>

Skin corrosion/irritation : Causes severe skin burns.  
pH: ≈ 11

# Ampreg 3X Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Serious eye damage/irritation	: Causes serious eye damage. pH: $\approx$ 11
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

#### Amines, polyethylenepoly-, triethylenetetramine fraction (90640-67-8)

LC50 fish 1	330 mg/l
EC50 Daphnia 1	31.1 mg/l
EC50 72h algae (1)	20 mg/l
NOEC chronic algae	< 2.5 mg/l

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

EC50 Daphnia 1	14.6 – 21.5 mg/l (48 h - Species: Daphnia magna [semi-static])
EC50 72h algae (1)	37 mg/l (Species: Desmodesmus subspicatus)

#### benzyl alcohol (100-51-6)

LC50 fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)
EC50 72h algae (1)	700 mg/l

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

Partition coefficient n-octanol/water (Log Pow)	0.79 (at 23 °C)
---	-----------------

#### benzyl alcohol (100-51-6)

Partition coefficient n-octanol/water (Log Pow)	1.1
---	-----

### 12.4. Mobility in soil

No additional information available

# Ampreg 3X Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available




## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

ADR	IMDG	IATA
<b>14.1. UN number</b>		
UN 2735	UN 2735	UN 2735
<b>14.2. UN proper shipping name</b>		
POLYAMINES, LIQUID, CORROSIVE, N.O.S.	POLYAMINES, LIQUID, CORROSIVE, N.O.S.	Polyamines, liquid, corrosive, n.o.s.
<b>Transport document description</b>		
UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Propylene glycol diamine, 2-amino-, diether with Propylene ; 3-aminomethyl-3,5,5-trimethylcyclohexylamine), 8, II, (E)	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Propylene glycol diamine, 2-amino-, diether with Propylene ; 3-aminomethyl-3,5,5-trimethylcyclohexylamine), 8, II	UN 2735 Polyamines, liquid, corrosive, n.o.s. (Propylene glycol diamine, 2-amino-, diether with Propylene ; 3-aminomethyl-3,5,5-trimethylcyclohexylamine), 8, II
<b>14.3. Transport hazard class(es)</b>		
8	8	8
		
<b>14.4. Packing group</b>		
II	II	II
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

# Ampreg 3X Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: C7
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP15
Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP1, TP27
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Hazard identification number (Kemler No.)	: 80
Orange plates	:



Tunnel restriction code (ADR)	: E
EAC code	: 2X
APP code	: B

#### Transport by sea

Special provisions (IMDG)	: 274
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP1, TP27
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-B
Stowage category (IMDG)	: A
Segregation (IMDG)	: SG35
Properties and observations (IMDG)	: Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.

#### Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 8L

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

# Ampreg 3X Slow Hardener

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Acute Tox. 4 (Oral)	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. The information contained within this document is Gurit copyright and any distribution or publication beyond the recipient's organisation is prohibited without Gurit's prior written consent.