

June 2018

PRODUCT DATA SHEET

Product	G4 Damp Seal
Type	A moisture cured single part polyurethane varnish.
Intended Use	Used as damp-proof floor sealing, pond sealing, sealing concrete prior to fibre glass sheathing where alkali in concrete can react with resins.
Special Features	Also, an ideal coating for plug surfacing before taking mould as release agents and resins do not attack G4.
Preparation	G4 should be applied onto a bare, clean and dry substrate. Existing coatings, paint or other treatments should be removed. Any loose pointing in brick work should be replaced or worn areas in floors repaired.
Application	Apply by brush or roller.
Coats	For most sealing purposes 3 coats are recommended.
Drying Time	60-90 minutes.
Re-coating Time	Each coat can be reapplied when the surface is finger tacky. Do not allow 4 hours to elapse between coats.
Application Temp.	G4 can be applied in poor weather conditions, high humidity and at temperatures down to 0°C. Withstands temperatures up to 200°C with good chemical resistance
Coverage	500g/sq.m
Maintenance	Not applicable.
Compatibility	Compatible with G4 Thinners.
Settlement	Shake well before use.
Shelf-life/Storage	Many years if suitably stored unopened in original container. NOTE; this is a moisture-hardened product so storage life of opened tins is limited.
Hazards	Flammable. Irritant. Avoid contact with eyes and skin. Wear protective gloves and eye protection. In case of contact with eyes, immediately rinse with plenty of water and seek medical attention. After contact with skin, wash immediately with soap and water or a suitable skin cleanser. Keep out of reach of children. Avoid ignition sources. Do not spray. Do not inhale vapour. Full safety data available on request or from www.bondaglass.com
Clean-Up	Clean equipment with Rustins Cellulose Thinners. Turpentine or White Spirit are unsuitable.
Sizes	500g, 1kg, 2.5kg, 5kg and 25kg