



Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.bondaglass.com

June 2018

PRODUCT DATA SHEET

Product	Bonda Wood Seal
Type	A moisture cured single part polyurethane varnish.
Intended Use	To be applied for marine use. For wood for a non-porous finish.
Special Features	The coating is tough yet flexible, and has excellent adhesion to many woods, with a high gloss non-yellowing finish.
Preparation	Should be applied onto a bare, clean and dry substrate. Existing coatings, paint or other treatments should be removed.
Application	Apply by brush or roller.
Coats	3 coats are optimal.
Drying Time	60-90 minutes.
Re-coating Time	Each coat can be reapplied when the surface is finger tacky. Do not allow 4 hours to elapse between coats.
Application Temp.	Can be applied in poor weather conditions, high humidity and at temperatures down to 0°C.
Coverage	500g/sq.m.
Maintenance	Not applicable.
Compatibility	Not applicable.
Settlement	Shake well before use.
Shelf-life/Storage	Many years if suitably stored unopened in original container. NOTE; this is a moisture-hardened product so storage life of opened tins is limited.
Hazards	Flammable. Irritant. Avoid contact with eyes and skin. Wear protective gloves and eye protection. In case of contact with eyes, immediately rinse with plenty of water and seek medical attention. After contact with skin, wash immediately with soap and water or a suitable skin cleanser. Keep out of reach of children. Avoid ignition sources. Do not spray. Do not inhale vapour. Full safety data available on request or from www.bondaglass.com
Clean-Up	Clean equipment with Rustins Cellulose Thinners. Turpentine or White Spirit are unsuitable.
Sizes	250ml, 500ml, 1L and 2.5L