



✉ info@lemark.co.uk

☎ (UK) 01480 494540
(Int.) +44 1480 494540

🌐 www.lemark.co.uk

Le Mark Group Ltd., 1 Houghton Hill Ind., Sawtry Way,
Houghton, Cambridgeshire, PE28 2DH England

Registered in England 1761971 VAT No. GB 395772693

📘 🐦 📷 @lemarkgroup

ALUMINIUM FOIL TAPE

Product Description

A 30 micron soft tempered bright aluminium foil coated with a pure acrylic adhesive, particularly suited to very low temperatures, on a 60gsm honey glassine liner. Building Regulations Class 0 approved which correlates to EN13501- 1 Class B.

Part number: AF600

Construction	Carrier:	30µ soft tempered bright aluminium foil
	Adhesive:	WM1070 pure acrylic permanent
	Release liner:	60gsm siliconised honey glassine
	Tape Thickness:	0.060 mm (without liner)
	Carrier Thickness:	0.030 mm
	Adhesive colour:	clear

Typical Application

This product is recommended where a moisture barrier is required.

Peel Adhesion Steel (24 hours) FINAT FTM1	-	20 N/25mm
Initial Tack Steel FINAT FTM9	-	10 N/25mm
Static Shear (hrs @ 1kg) FINAT FTM8	-	30 hours
Recommended temp. application range	-	5 to 38 °C
Shelf Life	-	12 months PSMA conditions

TAPES

LABELS

FLOORS

CREW WEAR

Storage

This item should be stored at room temperature, away from direct sunlight and damp.

Disclaimer

PLEASE NOTE: Stated performance figures and specification are based on average values and should not be regarded as maximum or minimum values. Measurements are approximate. Due to the nature of this product, performance may deteriorate over time. Due to varying application environments, the suggested uses should be considered as a general guide only. We recommend all users assess the suitability of our products for their individual application. Although we make all reasonable efforts to ensure the accuracy of information shown at time of print, we recommend contacting us for up to date product information prior to ordering.

Version Number: 1

Last revision date: 08/10/24

Approved by: E. Morton

TAPES

LABELS

FLOORS

CREW WEAR