

TECHNICAL  
PRODUCT DATASHEET

UPDATED: 23/12/2020

## Vega™

## 30cm Latex gauntlet with cotton flock lining

Lightweight but durable natural rubber gloves with a cotton flock lining to increase comfort and help absorb perspiration. Embossed Powergrip™ honeycomb coating acts to improve grip in wet and dry conditions whilst maintaining extra sensitivity and overall dexterity. Anatomically shaped to ensure comfort, flexibility and to reduce hand fatigue during prolonged periods of use. A rolled cuff offers drip protection, increased glove strength when donning and helps reduce roll-down.



## FEATURES AND TECHNOLOGY

CHEMICAL  
PROTECTIONRETAIL  
PACKAGED

WATERPROOF



POWERGRIP

FLOCK  
LINED

LATEX

LATEX

## TYPICAL INDUSTRIES

GENERAL  
PURPOSE

MANUFACTURING



RETAIL



AGRICULTURE

FOOD  
PROCESSING

JANITORIAL

## TECHNICAL INFORMATION

ORDER REF #	G/VEGA
COATING MATERIAL	N/A
PACKING	PER PACK: 10 x Pair
	PER CASE: 100 x Pair
SIZES AVAILABLE	7-7.5, 8-8.5, 9-9.5, 10-10.5
EU TYPE CERTIFICATION BY	SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland (Notified Body No. 2777)

## CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)

EN388:2016



1010X

Abrasion (0-4)  
Cut (0-5)  
Tear (0-4)  
Puncture (0-4)  
TDM Cut (A-F)

EN388:2003\*



1010

Abrasion (0-4)  
Cut (0-5)  
Tear (0-4)  
Puncture (0-4)

EN ISO 374-1  
:2016 / TYPE A

KLMPST

EN ISO  
374-5:2016Protection against  
bacteria & fungi - **PASS**Protection against viruses - **N/A**

0120



CAT III



<sup>1</sup> 'X' denotes not tested.  
<sup>2</sup> \* Where applicable, EN388:2016 scores take precedent and are ongoing.  
<sup>3</sup> There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.



Phone: +44 (0)1902 451 451

Fax: +44 (0)1902 451 271

Email: sales@ultimateindustrial.co.uk

Web: www.ultimateindustrial.co.uk

Ultimate  
IndustrialLeadership in  
PROTECTION.™

© 2020. Ultimate Cleaners (Industrial) Ltd.  
Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK.  
Registered in England No. 2035621



Ultimate  
Industrial

HAND PROTECTION RANGE



# TECHNICAL PRODUCT DATASHEET

CHEMICAL PROTECTION



UPDATED: 23/12/2020

## CERTIFICATION LEGENDS

### EN388:2016



\* For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

### EN ISO 374-1 :2016 / TYPE



A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulphide
F	Toluene
G	Diethylamine
H	Tetrahydrofuran
I	Ethyl Acetate

### EN ISO 374-5:2016



**TYPE A** - Gloves have achieved level 2 or greater against six of the chemicals listed in EN ISO 374-1 (below). The tested chemicals are identified by their code letters under the flask pictogram.

**TYPE B** - Achieved level 2 or greater against at least **three** of the chemicals.

**TYPE C** - Achieved at least a level 1 against **one** of the chemicals.

J	n-Heptane
K	Sodium Hydroxide (40%)
L	Sulphuric Acid (96%)
M	Nitric Acid (65%)
N	Acetic Acid (99%)
O	Ammonium Hydroxide (25%)
P	Hydrogen Peroxide (30%)
S	Hydrofluoric Acid (40%)
T	Formaldehyde (37%)

### EN407:2004



### EN511:2006



\* For details regarding maximum permissible user exposure, see separate sheet.

<sup>1</sup> Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. <sup>2</sup> 'X' denotes Not Tested. <sup>3</sup> Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.

## FURTHER INFORMATION

**STORAGE / TRANSPORT:** Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

**PRECAUTIONS BEFORE USE:** 1. Gloves should not be used when there is a risk of entanglement with moving machine parts. 2. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 3. The gloves should not come in contact with a naked flame or fire. 4. Do not subject to high speed or serrated blades. 5. Always read enclosed user instructions before using these gloves. 6. When used, protective gloves may provide less resistance to the dangerous chemicals due to changes in physical properties. 7. Movements, snagging, rubbing, degradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves. 9. This product has not been tested against viruses.

**CONSTITUENTS / ALLERGIES:** Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately.

**WARNING:** This product contains natural rubber latex which may cause allergic reactions. If affected, discontinue use immediately and seek medical advice.

## FOOD TEST INFORMATION

Details of the suitability for contact with various food categories as detailed in EEC Directive are available on request. Please quote product reference when enquiring.

